


■ Features


- ✚ Four 12VDC individually fused outputs
- ✚ Circuit Short protection
- ✚ Individual LED's for each output
- ✚ Uninterrupted Power Supply
- ✚ Battery back up
- ✚ Easy installation saves time and eliminates costly labor
- ✚ Spare fuses included
- ✚ 2 years warranty

■ Specification

Input Voltage	AC90-264V
Input Voltage Frequency	50/60Hz
Output Specification	
Output Voltage	12VDC+15%
Total Output Current	5A(1A/output,4 channels for 4 sets security cameras)
Total Outputs	60W
Fuse Type	Glass Fuse
Fuse Rating	1Amps/250VAC
Protection	
General Protection	each output has individual fuse and LED indicator, when problem occurs, only affect the individual output, other outputs still working
Circuit Short Protection	when short condition occurs, individual fuse will open the circuit,when condition removed, replacing another new fuse will back to close.
Over-load protection	105-135%hiccup mode,auto-recovery
Over-voltage protection	115-135%,Shut down o/p voltage, re-power on to recover
UPS function	High efficiency charge, Battery can be charged more than 90% full
	Cut charging automatically when finish charge, protect battery from overcharge
	Utility Power and battery switch automatically
	Cold start function, battery can start UPS when utility power cut

General Specifications	
Working temperature and humidity	-10℃~+60℃, 20%~80%RH
Store temperature and humidity	-20℃~+85℃,10%~90%RH
Application	
CCTV	Camera, PTZ, IR Illuminators, Video Process Equipment, etc.

■ **Shape and installation dimension**



■ **manual**

Multiple View, More attention!

Mulview Technology Limited

<http://www.mtlcctv.com>

TEL:0086-755-88849659 FAX:0086-755-83722362 E-mail:mulviewcctv@gmail.com,sales@mtlcctv.com