



■ Features

Features:

- Universal AC input voltage
- Small volume, low weight, high efficiency
- Protections: short circuit/over load
- cooling by free air convection
- LED indicator for power on
- 100% full load burn-in test
- 2 Years warranty

■ Specification

Model		MS-25-12	MS-25-15	MS-25-24	-----
output	DC voltage	12V	15V	24V	-----
	Voltage tolerance	±1%	±1%	±1%	-----
	Rated current	2.1A	1.7A	1.1A	-----
	Current range	0~1.3A	0~1.7A	0~1.1A	-----
	Rated power	25.2W	25.5W	26.4W	-----
	Ripple&noise	100mvp-p	120mvp-p	150mvp-p	-----
	DC voltage ADJ. range	±10%	±10%	±10%	-----
input	Voltage range	90~264VAC, 235~373VDC			
	frequency	47~63HZ			
	AC current	0.35A/230VAC			
	efficiency	78%	78%	80%	-----
	Inrush current	Cold start current 30A/230VAC			
	Leakage current	< 0.5mA/240VAC			
protection	overload	Rated output power 110%~135% start over load protection protection type :part layer type current limit, auto-recovery after fault condition is removed			
	-----	-----			
	-----	-----			
environment	Working temp, humidity	-10°C~+60°C, 20%~90%RH			
	Storage temp, humidity	-20°C~+85°C, 10%~95%RH non-condensing			

	Withstand vibration	10~500HZ, 2G10min/1cycle, period for 60 minutes, each axes
safety	Withstand voltage	I/P-O/P:1.5KVAC I/P-FG:1.5KVAC O/P-FG:0.5KVAC
	Isolation resistance	I/P-O/P, I/P-FG, O/P-FG:100Mohms/500VDC
Fit standard	Safety standard	Compliance toUL1012
	EMC standard	Compliance toEN55022, CLASSA
others	Dimension	84*58*31mm (L*W*H)
	Weight/packing	0.15kg/80pcs/13kg/0.024m ³ /0.87CUFT
note	<p>1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and25° Cof ambient temperature.</p> <p>2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.</p> <p>3. Tolerance : includes set up tolerance, line regulation and load regulation</p>	

Mulview Technology Limited

<http://www.mtlcctv.com>

TEL: 0086-755-88849659 FAX: 0086-755-83722362 E-mail: sales@mtlcctv.com